

TYPHOON EVO 220 LED TWIN

INSTALLATION RECOMMENDATIONS AND TECHNICAL CHARACTERISTICS

EVO
by **SACH**



INSTALLATION RECOMMENDATIONS TYPHOON EVO 220 LED

INSTALLATION RECOMMENDATIONS	MOTOR 220 TWIN
HOUSE(M ²)	UP TO 900 M ²
FURTHEST INLET VALVE (M ⁻)	60 M ⁻
APPROXIMATE NO.OF INLET VALVES	20

TECHNICAL CHARACTERISTICS TYPHOON EVO 220 LED

MOTOR	THROUGH FLOW HS
-------	-----------------

MODELS ASSEMBLED THROUGH FLOW HS (HIDE SPEED) OR DIRECT MOTORS. THE COOLING AIR AND THE AIR VACUUMED HAVE THE SAME CIRCUIT. ONLY ONE AIR INLET. THE FAN IS COOLED BY THE AIR THAT HAVE BEEN VACUUMED BEFORE.

SACH TYPHOON	220 LED TWIN
POWER (W)	2200
FLOW (M ³ /H)	294
DEPRESSION (MM/H ² O)	2500
DIAMETER (MM)	380
HEIGHT (MM)	940
SURFACE(M ² HEPA FILTER)	0.75
TANK CAP. (L)	20
WEIGHT (KG)	20